Article Code: C1S0000





Dimensions	Weight	Colours
H1425 x Ø194 mm	42.5 kg	RAL 7016 (Charcoal Grey)
Protection Degree	Material	Insulation
-	Steel >< 6 mm	Class II
Ventilation	Locking	Temperature
Natural	Special lock	-10℃ to +55℃

DESCRIPTION

The City1 controller without automation is capable to integrate position lights, control actuators and / or operation logic.

This City1 controller is normally associated with a cabinet or another controller (City3, 5 or 6) with built-in PLC (U100, U200 or Logo!)

The City1 controller is meant to be fixed to the ground on its embedding base (7).

Technical compartment (2) is accessible from the front. A trap door opens onto a push button to force descent of bollard. Finally, a polycarbonate (or aluminium) printed front face with a position light red/amber and/or control actuators.

The controller is delivered without control actuators. These are available as options.

COMPONENTS

- 1- City1 controller,
- 2- Access to technical components, lock,
- 3- Emergency trap door with special square imprint for fire-fighters,
- 4- Polycarbonate front face, not printed, (dimensions 258 x 140 mm),
- 5- Key to emergency trap door,
- 6- Key to technical compartment,
- 7- Embedding base.

OPTIONS & ACCESSORIES

- Colours: other RAL shades available as options,
- Position lights: red / amber,
- RE432 radio receiver,
- Beepers 1, 2 or 4 channels (ex. (8) (9)),
- Antenna 433.92 MHz,
- Key selector,
- Keypad,
- Card reader,
- Logical operation
- Communication tools (analog or digital intercom),
- Switch to force descent.

SURFACE FINISH

Primer zinc coating to increase resistance to corrosion and add on adherence to the surface

Thermosetting polyester powder paint, matt finish,

Standard colour: Charcoal grey RAL 7016

















Z.A. du Couquiou - 84320 ENTRAIGUES - France Tel. +33 490 480 800 - Fax +33 490 480 088

e-mail: export@urbaco.fr www.urbaco.fr