

# PRODUCT SHEET

Position light

*Wall-mounted or Post-Mounted*

## DESCRIPTION

Ø100mm traffic lights allow to check the position of the bollard on an access managed by PLC. It can be either red / orange, or red / green (according to the country).

## LIGHTS UNIT CHARACTERISTICS

- Material :** Stainless steel cast / Polycarbonate UV treated
- Colour :** Black
- Dimensions:** 127 x 323 x 114 mm
- Weight :** 2,3 kg
- Classification :** Class II (NF EN 650598-1)
- Voltage :** 24V ac
- Power/Consumption :** 2,2 W / 100 mA.
- Light source :** High intensity Ø5mm LEDS complying with NFP 99-200 and EN 12368 standards
- Light intensity :** Red 37 cd - yellow 45 cd - green 61 cd
- IP Rating :** IP55

## POST CHARACTERISTICS

- Dimensions :** Ø89mm - H1395mm
- Material :** Steel (thickness 3 mm)
- Finishing :** RAL 7016
- Fixing :** 3 fixing points
- Connection:** Pre-wired for easy connection. The cables are hidden in the tube and coming out from the bottom
- Weight :** 9 kg

## WALL BRACKET CHARACTERISTICS

- Dimensions :** L89mm - H300mm
- Material :** Steel
- Fixing :** 2 fixing points



## VERSIONS & LIGHT COLORS :

	Wall bracket	Single post	Double post
Red / Orange	CMF1RO08	CPF1RO08	CPF2RO08
Red / Green	CMF1RV08	CPF1RV08	CPF2RV08



## EXPLODED VIEW OF POSITION LIGHTS MODULE :

